

Kampa |  DOMETIC

TENTS

BREAN CLASSIC AIR






SUITABLE FOR:

BREAN CLASSIC AIR

3 & 4

| | | |
|-----------|------------------------------------|---|
| EN | Brean Classic AIR 3 & 4 | |
| | User Guide | 3 |



Welcome

Thank you for purchasing your Kampa Dometic AirFrame tent. Please read these instructions carefully before attempting to set up your tent and retain for future reference. If used properly, your tent should give you years of trouble free use. We recommend that your tent is insured against accidental and storm damage as this is not covered by the warranty.

IMPORTANT - PLEASE READ:

Under certain conditions all tents will suffer from internal condensation. Depending upon the atmospheric conditions, the weather and the amount of moisture in the ground, the condensation could be quite severe and is commonly mistaken for leaking, especially as it can run down the inside of the roof and drips off ties tapes and other internal fittings. If you suspect your tent is leaking it is almost certainly condensation.



Your tent is made from breathable polyester/cotton material that requires some preparation before first use to maximise its weatherproofing. Before first use fully set up the tent, preferably when heavy rain is expected and allow the tent to become thoroughly wet. This process is known as 'weathering'. If necessary you could use a hose pipe with a fine spray. This wetting tightens the fabric and allows the cotton in the sewing thread to swell and fill the holes made by the sewing needle. Allow the tent to thoroughly dry before packing away. Your tent's weatherproofing will improve with subsequent soakings.

This tent is designed for use in light to moderate weather. During very strong winds we recommend that you take your tent down. The tent is designed for touring use; it is not designed for static or commercial use. We recommend a trial run before using your tent for the first time. This will allow you to familiarise yourself with the tent, its set up and any limitations the tent may have for your particular use.



BEFORE USING FOR THE FIRST TIME PLEASE CHECK THE CONTENTS OF YOUR TENT

- Tent
- Central Ridge Pole
- Aluminium Front Canopy Pole
- Inner tent
- Hand Pump
- Peg Bag
- Carry Bag

The inner tent may already be attached to the tent and can be left attached for take down and setup.

If you are missing any parts please contact your supplying dealer.

Siting

Choose a site that is flat and, if possible, protected from the wind. Try to clear the site of sharp stones to avoid damaging the groundsheet. A footprint groundsheet is available as an optional extra - please see your dealer for more information. Try to set up your tent with the doors facing away from the wind. Avoid pitching under trees as falling branches, sap, etc could damage your tent.

Set-Up

To protect your tent from dirt and damage it may be beneficial to lay a footprint (available as an optional extra) or groundsheet down before unpacking.

Unpack the tent and separate and identify the different parts.

Assemble the aluminium canopy pole, this is shock-corded and just needs slotting together. Ensure that each pole is fully inserted into the adjoining pole.

Unroll and lay the tent out in the required position. Peg each corner of the tent (see Diagram 1A), highlighted by the blue QuickPitch pegging points. Ensure that you tension the tent between the pegs and making sure that the tent keeps its rectangular shape. You will probably need to re-peg later.

IMPORTANT:

It is important that whilst unscrewing/replacing the inflation/deflation valve that the valve does not spin in the AirPole. You can prevent this from happening by holding the valve in place where it meets the AirPole. If the valve spins it will twist the inflation tube in the pole and may lead to premature failure. If you suspect this has happened do not inflate your tent before untwisting the tube. Unscrew the valve from the AirPole and check that the inflation tube is not twisted. Before replacing the valve ensure that the black sealing washer is in place.



WARNING:

NEVER OPEN THE ZIP ON THE INNER TUBES WHILST THE POLES ARE INFLATED. THIS WILL RESULT IN THE POLE BURSTING.

Undo the front door to allow air into the tent.

Starting from one end of the tent, unscrew the top cap, of the inflation valve, and attach the pump nozzle (2). Pump up each AirPole (3). The pump has a pressure gauge and each AirPole should be inflated to 7-8 PSI (0.48-0.55 BAR). As each AirPole is inflated the tent will lift. It is normally necessary to go inside the tent and to push the poles upwards so that the AirPoles can assume their correct shape.

Once all the AirPoles have sprung outwards, assuming their correct shape, detach the pump from the tent and tighten the outer valve cap on each inflation point. It is important that these are tight to prevent the seepage of air.

You may need to use a guy rope to keep the tent upright in place whilst pegging.

Close all doors and entrances and check the positioning of the corner pegs again. If necessary re-peg to ensure that the groundsheet is taut inside the tent.

Peg all the intermediate pegging points (see Diagram 1B) ensuring that each side is straight.

Slide the aluminium canopy pole into the sleeve on the front of the tent (4). Fit each end into the 'cup' located on the airpoles.

QuickPitch Guying/Guy Lines

Your tent comes with a QuickPitch guying system. We recommend that these are used at all times. Peg the straps (see Diagram 1C) so that the tent is under tension without distorting the shape, they should run in-line

with the seams. The QuickPitch straps can be adjusted using the buckles. DO NOT allow children to play around your tent. QuickPitch straps are a trip hazard. In very windy conditions it is possible to pag the tent at the base of each pole.

Peg any remaining guy lines. The guy lines can be adjusted using the runners. They should be secured using suitable pegs and the guy line should generally be pegged in line with the seam of the tent it starts from. Check the guy lines from time to time to ensure that they are still adequately tensioned.

Central Ridge Pole

Inflate the central ridge pole to 7-8 PSI (0.48-0.55 BAR) and locate in the peak of the tent between the front and middle pole (5). There are velcro pads at each that attach to the velcro on the pole sleeves. ENsure the valve is pointing away from the roof panel.

Inner Tent

If the inner tent is not already installed, take the inner tent inside and suspend from the colour coded buckles (6). Attach the remaining suspension points.


Attach the base of the inners to the corresponding buckles on the groundsheet. It will be easier to attach the rear points before fully suspending the inner tent.

The inner tent can remain permanently installed whilst the tent is deflated and inflated.

Pegs

The tent comes complete with general purpose pegs. These will be suitable for many sites but there will be some instances where different pegs will be necessary. Your dealer will stock a range of pegs suitable for different types of ground. For maximum effectiveness, pegs should be driven into the ground at a 45° angle away from the pegging point.


Optional Canopy



An optional front canopy is available for the Brean 3 Classic AIR (Model No. CV3142) and Brean 4 Classic AIR (Model No. CV3141).

To Set-up:

1. Zip the canopy onto the front of the tent.
2. Unscrew the top cap, of the inflation valve, and attach the pump nozzle (2). Pump up the AirPole (3). The pump has a pressure gauge and the AirPole should be inflated to 7-8 PSI (0.48-0.55 BAR).
3. Peg the rear pegging points on the canopy (2A).
4. Peg the front QuickPitch pegging points (2B) ensuring the canopy sides are in-line with the tent. Pull on the blue webbing straps to tension the canopy.
5. Peg any remaining pegging points (2C).
6. Attach the Storm Tie-Down Straps to the side-release buckles located on the front of the canopy (4). Ensure that the storm straps are pegged under tension but not so that it distorts the shape of the tent or canopy.
7. Install the canopy groundsheet.



Rain

We make our tents as resistant to the weather as possible. Occasionally you may find slight leakage. This is not a fault with the manufacturing process or materials and can normally be rectified by spot treating the seam with seam sealant (see below).

Seams

Please refer to the beginning of this guide relating to weathering. Your tent will need to be weathered before use to be as weatherproof as possible. Follow the instructions in this section. If a seam is still leaking, particularly around tie tapes, a waterproofing spray can be used; your retailer will stock waterproofing spray.

Suitability

This tent is designed for use in light to moderate weather. During very strong winds or snowfall we recommend that you take your tent down. The tent is designed for occasional use; it is not designed for static or commercial use.

UV Degradation

Tent fabrics can be weakened by prolonged exposure to sunlight. Under normal holiday use your tent will give long service but use for extended periods in strong sunlight will soon cause deterioration. In those cases it would be wise to use a site as shaded as possible. UV degradation is not covered under the warranty. The warranty does not cover tents used on permanent sites, displays or for commercial purposes.

Condensation

Your tent is manufactured using a breathable material and is much less likely to be affected by condensation than fully synthetic tents. If you experience any condensation you should ensure that all the vents are open.



SAFETY

DO NOT COOK IN THE TENT OR USE NAKED FLAMES. READ AND UNDERSTAND THE FIRE PRECAUTIONS LABEL SEWN INTO THE INSIDE OF THE TENT.

Deflation

To pack away the tent

1. Close all doors and openings, including those on the inner tent/s.
2. Close all window blinds.
3. Un-peg the guy lines and tie them neatly to avoid future tangling.
4. Un-peg the intermediate pegging points but keep the four corners in place.
5. Open the valves on each pole. The tent will start to deflate. Wait until most of the air has been expelled.
6. Un-peg the four corners.
7. Fold/roll the tent towards the deflation valves to expel more air and then roll to fit in the carry bag.
8. Ensure that the tent is totally dry before storing in a cool, dry, dark space: if possible opened out.

Care

Tents are best stored opened out. Air fully and ensure it is totally dry before packing away. Store in a well ventilated dry place. A wet/damp tent will develop mildew surprisingly quickly.

Dirty tents can be washed using clean water and a soft brush. Do not scrub and never use detergents.

The AirPoles do not need any maintenance but should be protected from damage during storage. Damage due to improper use, wind damage or neglect is not covered under the warranty. Have any damage repaired at the first opportunity.

Zips should be treated with care, use two hands to close and open and never tread on them. Never force a zip. We strongly recommend that you carry a comprehensive spares kit including silicone waterproof spray, seam sealer and tape for repairing the AirPoles.

Repairs to the tent should be made by a company recommended by Kampa Dometic or your supplying dealer. Repairs and alterations made by an unauthorised company may invalidate your warranty.

In the event of a puncture

1. Undo the inflation/deflation valve from the pole and re-attach ensuring that the valve is firmly connected.
2. Re-inflate the AirPole.
3. If tightening the hose fittings does not solve the problem then the AirPole may be punctured.

To remove an Airpole

1. Unzip the outer sleeve holding the AirPole.
2. Remove the AirPole.
3. Unzip the protection sleeve of the AirPole, whilst deflated, to expose the inflatable bladder.
4. Locate the puncture. This is made easier if you inflate the bladder. For small holes it may be necessary to submerge the bladder in water.
5. Once located, the bladder can be repaired using repair tape. We recommend Kampa Dometic Awning Repair Tape - available from your retailer.

The repair can be enhanced by using a combination of the tape with Kampa Dometic Repair Solution. Follow the manufacturers instructions to repair.

Another alternative is to replace the tube. Spares are available from your retailer or direct from Kampa Dometic. Once a repair or replacement has been made, the AirPole can simply be zipped back into the outer sleeve.

Troubleshooting

| Problem | Solutions |
|----------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Difficulty in pumping up the awning | <ol style="list-style-type: none"> 1. The inflation valve is not fully screwed into the AirPole. 2. The AirPole is twisted at the valve. This may also be indicated by a noise. DO NOT continue to inflate until the AirPole has been untwisted (see page 4). |
| If you suspect an air leak | <ol style="list-style-type: none"> 1. Check that the inflation valve is properly screwed in and that the black 'O' ring seal is in place. 2. Check that the top cap on the inflation valve is done up tightly. |
| If you think your awning has a water leak | Most suspected leakage is actually condensation (see condensation section of this manual). This forms on the inside of the awning fabric. Try to increase the ventilation by opening doors and ventilation ports. Do not cook in your awning. |
| If your awning has a water leak at specific points/areas | Seam sealant can be applied to any localised areas where a leak may have developed. Seam sealant is available through your retailer. |

Mobile living made easy.



dometic.com

**YOUR LOCAL
DEALER**

dometic.com/dealer

**YOUR LOCAL
SUPPORT**

dometic.com/contact

**YOUR LOCAL
SALES OFFICE**

dometic.com/sales-office
